



boa. 3D-dry  
flexstep®

SIEVI ROLLER+ S3

43-52156-113-08M

39-47 EN ISO 20345: S3 SRC

Sievi Roller features a patented easy-to-use and durable Boa® tightening mechanism. The Boa® mechanism provides more comfort for the wearer: a turn of the dial and your shoes fit perfectly. The shoes are also fast and easy to put on and take off: the laces loosen by simply lifting the dial.





#### Toecap, composite

The toecap protects toes from falling objects and compression. Meets the requirements of the EN ISO 20345:2011 standard: shock resistance is 200 J and resistance to compression 15000 N.

Toecap made of composite material is completely metal free and insulates well against heat and cold.



#### Penetration resistant midsole, composite

The penetration resistance fulfills the same EN ISO 20345:2011 requirements as traditional midsole made of steel. Steel, however, gives greater penetration resistance, which is why Sievi recommends a steel midsole for the more demanding conditions (e.g. construction industry).



#### Resistance to oil and many chemicals

Sievi's sole resists oil and many chemicals. The oil resistance of Sievi footwear meets the requirements of the EN ISO 20345:2011 standard.



#### Antistatic

Footwear designed with antistatic features, discharges the body's static electricity up to tolerances of 100 k $\Omega$  - 1000 M $\Omega$ .



#### Water repellent

The upper material used in this footwear is water repellent. Its water resistance meets the requirements of the EN ISO 20345:2011 standard.



#### Shock-absorbing heel

The shock-absorbing heel area protects the feet and the skeletal system against stress. The product meets the requirements of EN ISO 20345:2011 and EN ISO 20347:2012: the shock absorption capacity of the footwear is at least 20 J. The cushioning effect is guaranteed by the use of FlexStep® sole material in all Sievi footwear.



#### Sole material PU/TPU

The double density sole consists of polyurethane and elastic thermoplastic polyurethane. The outsole is wear resistant and the mid-layer is of shock absorbing FlexStep® material.



#### DUAL insole

The Sievi DUAL Comfort insole has shock absorbing cushions made of PORON® material which adds comfort to your feet and back.



#### Microfibre

The upper material of the footwear is microfibre, which is fast drying and very resistant to frequent washing.



#### ESD

Through its sole construction, ESD footwear provides a safe and controlled method of discharging the body's static electricity. The tolerances for the resistance of Sievi footwear are stricter (100 k $\Omega$ -35 M $\Omega$ ) than for ordinary antistatic footwear (IEC 61340-5-1).



#### BOA® Closure System – more user comfort

Easy to use and durable, the patented Boa® Closure System significantly increases the wearer comfort of the footwear. Turn the button to achieve the perfect fit.



#### Dry feet with 3D-dry

3D-dry lining, developed by Sievi, transfers moisture from the foot to the second layer of the lining and further through the upper and away from the shoe thus keeping your feet drier and more comfortable.



#### FlexStep® – Grip and flexibility to work

The microporous FlexStep® sole material, developed by Sievi has been re-designed. The re-designed sole material maintains its excellent shock absorbing properties and flexibility in freezing conditions more efficient. The footwear sole therefore remains softer, even in heavy freezing conditions, and maintains excellent friction on slippery surfaces. The construction of the FlexStep® flexible sole eliminates stress and shocks to the feet and spine, helping to prevent foot and back pains and thereby improving work efficiency. The FlexStep® flexible sole is featured on all Sievi footwear.